24 133

GROHTHERM®

DUAL FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM WITH CONTROL MODULE



STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE TurboStat® compact cartridge with wax thermoelement
- Thermostatic temperature control with GROHE SafeStop safety button at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- 6 1/4" Metal wall trim plate with GROHE QuickFix® (concealed mounting screws)
- · Metal trim angle adjustable up to 6°
- GROHE AquaDimmer (top handle) includes integrated shut off & 2-way diverter (2 discrete functions)
- ADA compliant lever handles
- Includes service stops
- 7.1gpm at 45psi
- Optional AquaDimmer stop ring for shared function (14 060 000) (sold separately)
- Requires GROHE Rapido® SmartBox (35 601 000) (sold separately)



PRODUCT FEATURES:



GROHE StarLight®



GROHE QuickFix®



GROHE TurboStat®

CERTIFICATIONS:



- ADA
- CEC Certified
- Massachusetts Plumbing Board Approved
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1ASME A112.1016
- Complies with lead plumbing laws

AVAILABLE FINISHES:

24133000

GROHE StarLight® Chrome

241332430



24133EN0

Brushed Nickel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 06-03-2022

US

Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet, go to www.grohe.us.

Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



GROHTHERM®

Pure Freude an Wasser GROHE

DUAL FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

TECHNICAL DATA:

Product Height 6-1/4 in

Product Length 1-11/16 in

Product Width 6-1/4 in

