mr.steam[®]

TECHNICAL SPECIFICATIONS

iTempoPlus® Controls

iTempoPlus controls flush mount in the steam/shower enclosure through a 2 %" wide x 3%" high hole. iTempo controls can also be surface mounted.

iTempoPlus Controls Feature:

- Solid brass decorative cover with choice of square or round styles in designer finishes
- Digital display
- Programmable temperature
- AromaSteam Steamhead in matching finish and shape
- Compatibility with SteamLinx

- Soft touch keypad
- Low voltage operation
- Programmable steam bath duration
- Clock
- ON/OFF control for AromaSteam and Chroma72
- Two programmable presets

The iTempoPlus controls are designed to be installed inside or outside the steam room but is primarily installed inside the steam room. If the control is installed inside the steam room the control must be located:

- 4-5 feet above the floor
- in a location representative of the desired steam bathing temperatures. Do not locate the control above or near the Steamhead or direct steam emissions.

The control cable length is 30 feet. Insure that the control and/or steam generator are located accordingly.

An optional 60 ft. cable is available if required, PN 103990-60.

If the control is installed outside the steam room a Remote Temperature Probe Part Number MSTS must be installed inside the steam room.

FOR ILLUSTRATIVE PURPOSES ONLY. IMPORTANT NOTE: FOR SAFE AND TROUBLE

FREE INSTALLATION visit mrsteam.com before installation to download the Installation, Operation and Maintenance Manual or refer to the manual provided with the unit.

MODEL SHAPE FINISH PROJECT INFORMATION **RD** Round BB - Brushed Bronze Location: MS iTempoPlus BN - Brushed Nickel SQ Square Architect: ORB - Oil Rubbed Bronze Engineer: PB - Polished Brass Contractor: PC - Polished Chrome Submitted By: PN - Polished Nickel SB - Satin Brass Date: BK - Black Fascia Notes: WH - White Fascia MB - Matte Black RAW - Custom Plating

- iTempoPlus
- Tube of Silicone Sealant
- Steamhead

Ø5"

- Owner's Manual
- Control Cable (30 ft.)

Dimensions for round and square controls:





