






Category 3

Copper Installation

The best soldered joints come from the best cleaning and fluxing tools, as well as a careful and professional technique. Our solder, flux and cleaning tools are designed for the professional who takes pride in knowing just how to do the job right and chooses the highest quality products.

FLUX

No. 5 Paste Flux



- · Effective on all metals except aluminum, magnesium and stainless steel.
- 100% lead free.
- · Blended to clean surface oxidation.

Product No.	Size	Description	Ctn. Qty.
30011	1.7 oz.	No. 5 Flux	12
53017	1.7 oz.	No. 5 Flux w/ Brush - Carded	12
53200	1.7 oz.	No. 5 Flux w/ Brush - Carded*	12
30013	4 oz.	No. 5 Flux	24
30014	8 oz.	No. 5 Flux	24
30041	16 oz.	No. 5 Flux	12
30041D	16 oz.	No. 5 Flux – Display	12

^{*}Packaged without inner display carton.





- Formulated with the same high quality as No. 5. Oatey Safe Flo Alloy powder is added to pre-tin the copper pipe.
- Does not turn copper green.
- 100% lead free.
- Excellent for large diameter copper.



^{*}Packaged without inner display carton.



#53017 shown

(NSF.)

#30374 shown





#30133 show



U.S. Patent No. 6,752,309

H-20®5 Paste Flux

- · Water flushable.
- As thick as No. 5 flux.
- Meets ASTM B-813.

11100107101111	0.0.		
Product No.	Size	Description	Ctn. Qty.
30130	1.7 oz.	H-20 ⁵ Water Soluble Paste Flux	12
53067	1.7 oz.	H-20 ⁵ Water Soluble Paste Flux – Carded	12
30131	4 oz.	H-20 ⁵ Water Soluble Paste Flux	24
30132	8 oz.	H-20 ⁵ Water Soluble Paste Flux	24
30133	16 oz.	H-20 ⁵ Water Soluble Paste Flux	12





#30143 shown (NSF.) U.S. Patent No.

6,752,309

H-20[®]95 Water Soluble Tinning Flux

- Water soluble tinning flux base.
- · As thick as No. 5 flux.
- Solder powder added to pre-tin the pipe.

Product No.	Size	Description	Ctn. Qty.
30140	1.7 oz.	H-20 ⁹⁵ Water Soluble Tinning Flux	12
53068	1.7 oz.	H-20 ⁹⁵ Water Soluble Tinning Flux – Carded	12
30142	8 oz.	H-20 ⁹⁵ Water Soluble Tinning Flux	24
30143	16 oz.	H-20 ⁹⁵ Water Soluble Tinning Flux	12